

Convert – Sprayable Rust Converter

Safety Data Sheet

SECTION 1: Product and company identification

Product name : Convert – Sprayable Rust Converter
Use of the substance/mixture : Metal treatment
Product code : 0347
Company : Total Solutions
P.O. Box 240014
Milwaukee, WI 53224 - USA
T (414) 354-6417
Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Glycol Ether EB	(CAS No) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove the victim into fresh air.
First-aid measures after skin contact : Rinse skin with water/shower.
First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation : None under normal use.
Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion : Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Reactivity : Upon combustion: CO and CO₂ are formed.

Convert – Sprayable Rust Converter

Safety Data Sheet

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

- Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

- No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.
- Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep container closed when not in use. Keep only in original container.
- Storage area : Meet the legal requirements. Store in a cool area. Store in a well-ventilated place.
- Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

8.2. Exposure controls

- Personal protective equipment : Gloves. Safety glasses. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Beige, opaque emulsion.
- Odor : Bland odor
- Odor threshold : No data available

Convert – Sprayable Rust Converter

Safety Data Sheet

pH	: 1.5 - 3
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.06 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: <= 3 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 1.5 - 3

Serious eye damage/irritation : Not classified
pH: 1.5 - 3

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Glycol Ether EB (111-76-2)	
IARC group	3 - Not Classifiable

Convert – Sprayable Rust Converter

Safety Data Sheet

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified

Glycol Ether EB (111-76-2)	
NOAEL (oral,rat,90 days)	see comments
NOAEL (dermal,rat/rabbit,90 days)	see comments

Aspiration hazard : Not classified
Symptoms/injuries after inhalation : None under normal use.
Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion : Gastrointestinal complaints.
Likely routes of exposure : Skin and eyes contact

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Glycol Ether EB	CAS No 111-76-2	1-5%
-----------------	-----------------	------

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed

Convert – Sprayable Rust Converter

Safety Data Sheet


TOTAL
SOLUTIONS™

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.